

IN THE CLAIMS

Please cancel claims 2-9, 11-14, and 16, and amend remaining claims as shown below:

1 1. (Currently Amended) A computer-implemented method for generating a table of
2 contents for a document using information in said document, comprising ~~the steps of~~:
3 building a model of said document including an initial semantic structure;
4 detecting hierarchical changes in said semantic structure spanning different scales;
5 and
6 ordering said changes into entries in said table of contents based on scale span.

1 2-9. (Canceled)

1 10. (Currently Amended) The method of claim 1 wherein said building ~~step~~ further
2 comprises ~~the further steps of~~:
3 defining a vector of terms occurring in said document; and
4 mapping said document into a vector space by projecting scaled term occurrence
5 histogram data onto said vector of terms and summarizing said terms using
6 singular-value decomposition.

1 11-14. (Canceled)

1 15. (Currently Amended) The method of claim 1 wherein said detecting ~~step~~ further
2 comprises ~~the further steps of~~:

3 applying successively smaller scale filter windows to said model according to said
4 initial semantic structure to construct a map of said changes versus scale;
5 identifying local peaks in said contour map, said peaks being points of maximum
6 vector derivative magnitude;
7 tracing said local peaks back to a semantic structure change origin point; and
8 measuring a span of scales over which each said change exists.

1 16. (Canceled)

1 17. (Currently Amended) A system for generating a table of contents for a document using
2 information in said document, comprising:

3 means for building a model of said document including an initial semantic structure;
4 means for detecting hierarchical changes in said semantic structure spanning
5 different scales; and
6 means for ordering said changes into entries in said table of contents based on scale
7 span.

1 18. (Currently Amended) A computer program product comprising a machine-readable
2 medium having computer-executable program instructions thereon for generating a table of
3 contents for a document using information in said document, including:

4 a first code means for building a model of said document including an initial
5 semantic structure;

6 a second code means for detecting hierarchical changes in said semantic structure
7 spanning different scales; and

8 a third code means for ordering said changes into entries in said table of contents
9 based on scale span.